

Utförande: Vitlackerad metall. Bländskydd av matt akryl. Som tillbehör finns enkel- och dubbelasymmetriskt bländskydd.

Montage: Infälld i ventilerat alt. oventilerat undertak. Kompletteras med gavel för montage i fast tak alt. T-profil. Kan rampmonteras.

Anslutning: Snabbkopplingsplint 5x4mm². Överkopplingsbar.

Design: R. Aosta.

W	L/MM	KG	ART
14W/T5	581	2,7	7520-1-01
14W/T5	581	2,7	7520-1-01HFF
21W/T5	881	3,2	7520-3-01
21W/T5	881	3,2	7520-3-01HFF
28W/T5	1181	3,7	7520-5-01
28W/T5	1181	3,7	7520-5-01HFF
35W/T5	1481	4,2	7520-7-01
35W/T5	1481	4,2	7520-7-01HFF

HFF = Dimmbart driftdon. Fördunklas via SwitcDIM alt. DSI. Dali på begäran.
 HFF = Dimmable ballast SwitchDim/DSI, available with Dali on request.

TILLBEHÖR/ACCESSORIES

Rak koppling för rampontage i fast undertak <i>Straight connector</i>	97520-1-01
Gavel för montage i fast undertak/ <i>End panel</i>	97521-1-01
Gavel för montage i synlig T-profil <i>End panel for visible T-profile</i>	97522-1-01
Enkelasymmetrisk bländskydd L 581 <i>Single asymmetric diffuser L 581</i>	97524-1-01
Enkelasymmetrisk bländskydd L 881 <i>Single asymmetric diffuser L 881</i>	97524-3-01
Enkelasymmetrisk bländskydd L 1181 <i>Single asymmetric diffuser L 1181</i>	97524-5-01
Enkelasymmetrisk bländskydd L 1481 <i>Single asymmetric diffuser L 1481</i>	97524-7-01
Dubbelasymmetrisk bländskydd L 581 <i>Double asymmetric diffuser L 581</i>	97525-1-01
Dubbelasymmetrisk bländskydd L 881 <i>Double asymmetric diffuser L 881</i>	97525-3-01
Dubbelasymmetrisk bländskydd L 1181 <i>Double asymmetric diffuser L 1181</i>	97525-5-01
Dubbelasymmetrisk bländskydd L 1481 <i>Double asymmetric diffuser L 1481</i>	97525-7-01

Finish: White painted steel. Diffuser in matt acrylic. Single- or double-asymmetrical diffuser available as accessory.

Installation: Recess installation.

Connection: Snap-in terminal block 5x4mm². Two cable entries.

Design: R. Aosta.

